

COPILLOT SOL NG-L

Warm air heater for stable

Gas fired warm air heater for stable heating as fully automatic system with infrared flame monitoring, electrical ignition and supporting air blower and open combustion chamber for operation without exhaust system. The unit can be switched over from one to the other gas type by only changing the nozzle and new setting of pressure.

FEATURES

**Farm
homologation**



- Electric mains with shock-proof plug.
- Gas connection ¾" or ½" internal screw thread.
- Casing and combustion chamber made of stainless steel.
- Splash-proof switch box.
- Drive via room thermostat or ventilating control possible.
- Automatic ignition.
- Three-point suspension by adequate attachment eyes.
- **Clean Combustion** (DIN 33697, CO<0,003%V): Air quality in a stable is our priority.
- Low-maintenance burner.
- For **Natural Gas** and **LPG** (except for **NG-LE 10**)
- Extremely Secure Unit for each kind of animals.

TECHNICAL DATA

The great range **COPILLOT SOL NGL**: always any heater adapt to your stable.

Type of Unit	SOL NG-LE 10	SOL NG-L 30	SOL NG-L 50	SOL NG-L 80	SOL NG-L 100
Nominal Capacity	10kW	30kW.	50kW.	80kW.	100kW.
Air capacity	500m3/h	1.600m3/h	2.300m3/h	4.100m3/h	7.500m3/h
Supply Pressure	0,02bar	0,02bar o 0,05bar	0,02bar o 0,05bar	0,02bar o 0,05bar	0,02bar o 0,05bar
Connected load	–	2,33 Kg/h	3,89 Kg/h	6,23 Kg/h	7,78 Kg/h
Category	Natural Gas I2E	Natural Gas and LPG I3 B/P	Natural Gas and LPG I3 B/P	Natural Gas and LPG I3 B/P	Natural Gas and LPG I3 B/P
Rated Current	0,3A.	0,85A.	1,0A.	2,9A.	3,7A.
Dimensions mm.	500 x 450 x 450	990 x 445 x 312	990 x 510 x 365	1150 x 560 x 410	1250 x 640 x 510
Weight	16kg.	35kg.	41kg.	45kg.	56kg.
Electric Supply	230V / 50Hz.	230V / 50Hz.	230V / 50Hz.	230V / 50Hz.	230V / 50Hz.
Throw	15m.	30m.	40m.	50m.	60m.
Product Id. Nr.	CE-0085 / BN-0001	CE-0085 / BN-0001	CE-0085 / BN-0001	CE-0085 / BN-0001	CE-0085 / BN 0001

GAS FIRED AMBIENT HEATER